

Canon DR-7580 and DR-9080C

These Canon scanners can scan documents at high processing speeds without compromising image quality. The ADF can hold up to 500 A3 sheets; the ultrasonic double feed control and a mechanism to recognize stapled documents guarantee secure batch scanning.

Speeds have been considerably improved, both in black and white scanning and, in particular, in grey scale and colour scanning. These devices work at 75ppm or 90ppm respectively in black and white and grey scale, and the DR-9080C also scans 60 pages per minute in colour, thanks to the onboard JPEG compression. The 600dpi optical resolution guarantees excellent scanning results.

Working Environment

The Canon DR-7580 and DR-9080C scanners are compact, easy to use and reliable low volume production scanners, which offer an attractive price-performance ratio. They are suited for workloads between 2,000 and 9,000 pages per day in a wide range of business applications.

Top Features

- Ultrasonic double feed detection
- Stapled document detection (using Scanner-Stop)
- High scanning speed for black and white / greyscale (both scanners) and colour (DR-9080C)
- MultiStream function for simultaneous output in black and white and colour (DR-9080C)

Included

- ISIS and TWAIN drivers
- User Manual
- Power cable, USB connection cable
- CapturePerfect 3.0 imaging software



Accessories (not included)

- Imprinter (32 characters)
- Endorser ED600
- Barcode Module II
- Hard Counter
- Kofax VRS 4 Professional for Workgroup Scanning (DR-7580)
- Kofax VRS 4 Professional for Production Scanning (DR-9080C)

| | | |
|-------------------------|----------------------------------|----------------------------|
| Scanning mode | Duplex | |
| Document feed | ADF (500 sheets capacity) | |
| Document size | 55 x 70 mm to 305 x 422 mm (A3+) | |
| Optical resolution | 600dpi | |
| Speed (A4, Portrait) | Simplex DR-7580/DR-9080C | Duplex DR-7580/DR-9080C |
| B/W (200dpi) | 75ppm/90ppm | 120ipm/180ipm |
| Colour (200dpi) | 50ppm (DR-9080C) | 100ipm (DR-9080C) |
| Interface | Ultra SCSI and USB 2.0 | |
| Dimensions (WxDxH) | 460 x 525 x 310 mm | |
| Weight | 23 kg | |
| Noise level (operating) | < 75 dB(A) | |
| Noise level (stand-by) | < 40 dB(A) | |

